

Finishes

SHEETROCK® COVE CORNICE



Description

SHEETROCK® Cove is Knauf's lightweight paper face cove cornice. Using innovative core technology, SHEETROCK Cove is 5% lighter than previous Knauf Cove products* and has high strength-to-weight composite design.

Encased in a strong 100% recycled paper liner, SHEETROCK Cove provides a rigid cornice making carrying, handling and installing easy. Ideal for residential and commercial internal ceiling applications. Available in 55, 75 and 90mm profile sizes and up to 4.8m lengths.

*Compared to Knauf Standard Cove 55, 75 and 90mm

Cornice Specification

Feature	Description
Thickness	10mm thick members
Profiles	55mm, 75mm and 90mm
Lengths	55mm (3600mm, 4800mm) 75mm (3600mm, 4800mm, 5400mm) 90mm (3000mm, 3600mm, 4800mm, 5400mm)
Paper Colour	Buff
Mass (nominal)	55mm (58kg/100Lm) 75mm (90kg/100Lm) 90mm (118kg/100Lm)
VOC	Less than 0.5mg/m3 TVOC
GECA	N/A
Manufacture	Innovative core technology with high strength-to-weight composite design and encased in a strong 100% recycled paper. Manufactured to stringent Knauf product quality specifications

Advantages

- Lightweight, high strength-to-weight composite design
- Great rigidity for ease of handling and installation
- Easy to cut, mitre and clean up
- Consistent profiles with clean lines

Intended for

- Wall to ceiling applications.
- New residential or commercial construction
- Repair and alterations of existing buildings

Limitations

- Avoid exposure to excessive or continuous moisture before, during and after installation. Eliminate sources of moisture immediately
- Must be stored under cover and not in direct sunlight

Finishing and Decorating

- For high-quality finishing results, Knauf recommends the following products:
- Knauf Cornice Adhesive eg. Cornice Adhesive 45 or 60
- AS/NZS 2589: 2007 Gypsum linings – Application and Finishing, should be referred to in order to determine the level of finishing needed to ensure a surface properly prepared to accept the final decoration.

Installation

Refer to Knauf website **knaufapac.com**. or call TecASSIST® on **1800 811 222**

Compliance

- Qualifies as low VOC emitting material, less than 0.5mg/m³ TVOC
- Classified as non-hazardous in accordance with NOHSC Australia

Sustainability

Knauf products are manufactured from a combination of natural gypsum, and paper liner made from 100% reclaimed and recycled paper waste. Plasterboard waste can be reclaimed and recycled into new plasterboard, or reused as soil conditioner.

Volatile Organic Compounds (Voc) and Formaldehyde Minimisation

Knauf products, compounds and adhesives have been independently tested to confirm compliance with Green Star specification limits for VOCs.

References

For further health and safety instructions, refer to the Material Safety Data Sheet for this product, available from your Knauf sales office, TecASSIST® 1800 811 222 or **knaufapac.com**. In Emergencies Call **1800 033 111**. Poison Information **13 11 26**.